



N95 Respirator Mask (Sourced from Jackson Safety)

Important information from the manufacturer. Read before using. For a helpful video, courtesy of Keyline Industrial, scan the smartphone code to the left.



JACKSON SAFETY 1859 Bowles Ave. Suite 200 Fenton, MO 63026 (800) 428-8185



Type N95 NIOSH Approved Disposable Respirator Mask

WARNINGS - Read and understand before use.

- A properly selected respirator is essential to protect your health. Before using this or any
 product consult an Industrial Hygienist or Occupational Safety Professional to determine its
 suitability for your intended use.
- This product will not protect against gases or vapors. Do not use in spray paint operations.
- · Do not use in or around sand blasting.
- Do not use for protection against asbestos.
- This product does not supply oxygen. Use this respirator in a well ventilated area containing sufficient oxygen to support life.
- Do not use when concentrations of contaminants are unknown or immediately dangerous to life.
- Leave work area immediately if: (A) Breathing become difficult, or (B) Dizziness or other signs of distress occur.
- If user has any illness or disorders, consult a licensed medical doctor to determine suitability
- Facial hair and certain facial characteristics may prohibit effective use of this product.
- · Use only in accordance with instructions, labels and limitations relating to this product.
- · Do not alter or modify this product in any way.
- · Follow the manufacturer's instructions for fitting the respirator to the face.

1. Protection

N-95 Particulate Filter (95% filter efficiency level) effective against particulate aerosols free of oil; time use restrictions may apply.

2. Cautions and Limitations

- A Not for use in atmospheres containing less than 19.5% oxygen.
- B Not for use in atmospheres immediately dangerous to life or health.
- C Do not exceed maximum use concentrations established by regulatory standards.
- J- Failure to properly use and maintain this product could result in injury or death.
- M All approved respirators shall be selected, fitted, used and maintained in accordance with MSHA, OSHA and other applicable regulations.
- N Never substitute, modify, and or omit parts.
- Refer to users instructions and/or maintenance manuals for information on use and maintenance of these respirators.
- P NIOSH does not evaluate respirators for use as surgical masks.
- \$ Special or critical User's Instructions and/or specific use limitations apply. Refer to User's Instructions before donning.

IMPORTANT NOTICE TO PURCHASER

The following warranty is made in lieu of all other warranties expressed or implied, including but not limited to, the implied warranties of merchantability and fitness for purpose. Manufacturer warrant is this product to be free from defects. Manufacturer's only obligation shall be, at our option, to replace any portion proving defective or to refund the purchase price thereof. USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR HIS INTENDED USE, AND ASSUME ALL RISKS AND LIABILITY IN CONNECTION THEREWITH.

Respirator Fitting Instructions:

 Hold the respirator in hand with nosepiece at your fingertips, allowing the headbands to hang freely below your hand.



Press the respirator firmly against your face with the nosepiece on the bridge of your nose.



 Stretch and position the top band high on the back of your head. Stretch the bottom band over the head and position it below your ears.



 Using both hands, mold the metal nosepiece to the shape of your nose.



5. To test fit cup both hands over the respirator and exhale vigorously. If air flows around your nose, tighten the nosepiece, if air leaks around the edges; reposition the straps for a better fit.



Remember, careful observance of these fitting instructions is an important step in safe respirator use.

S- Special Instruction: The N95 Respirator without valve filtering face piece respirator has been manufactured by Aswan for Jackson Safety under TC-844-2022

IOTE: Before issuing any respirator to be worn, a face fit test must be performed. See OSHA regulations 1910.134 (e)(5). Prior to each use, filtering facepieces should be inspected to assure there are no holes in the breathing zone. Enlarged holes resulting from ripped or torn filter material around staple punctures are considered lamaged and should be discarded. Small punctures around the staples are normal and do not interfere with the respirator compliance with Part 84 approval. Mask hould not be worn for more than 8 hours.

How to Properly Put on and Take off a Disposable Respirator

WASH YOUR HANDS THOROUGHLY BEFORE PUTTING ON AND TAKING OFF THE RESPIRATOR.

If you have used a respirator before that fit you, use the same make, model and size.

Inspect the respirator for damage. If your respirator appears damaged, DO NOT USE IT. Replace it with a new one.

Do not allow facial hair, hair, jewelry, glasses, clothing, or anything else to prevent proper placement or come between your face and the respirator. Follow the instructions that come with your respirator.

Putting On The Respirator



Position the respirator in your hands with the nose piece at your fingertips.



Cup the respirator in your hand allowing the headbands to hang below your hand. Hold the respirator under your chin with the nosepiece up.



The top strap (on single or double strap respirators) goes over and rests at the top back of your head. The bottom strap is positioned around the neck and below the ears. Do not crisscross straps.



Place your fingertips from both hands at the top of the metal nose clip (if present). Slide fingertips down both sides of the metal strip to mold the nose area to the shape of your nose.

Checking Your Seal²



Place both hands over the respirator, take a quick breath in to check whether the respirator seals tightly to the face.



Place both hands completely over the respirator and exhale. If you feel leakage, there is not a proper seal.



If air leaks around the nose, readjust the nosepiece as described. If air leaks at the mask edges, re-adjust the straps along the sides of your head until a proper seal is achieved.



If you cannot achieve a proper seal due to air leakage, ask for help or try a different size or model.

Removing Your Respirator



DO NOT TOUCH the front of the respirator! It may be contaminated!



Remove by pulling the bottom strap over back of head, followed by the top strap, without touching the respirator.



Discard in waste container. WASH YOUR HANDS!

Employers must comply with the OSHA Respiratory Protection Standard, 29 CFR 1910.134 if respirators are used by employees performing work-related duties.

- 1 Manufacturer instructions for many NIOSH approved disposable respirators can be found at www.cdc.gov/niosh/npptl/topics/respirators/disp_part/
- 2 According to the manufacturer's recommendations

For more information call 1-800-CDC-INFO or go to http://www.cdc.gov/niosh/npptl/topics/respirators/







